

PIPE INSPECTIONS SYSTEM:

A.5061



• Sliding camera for optical inspection of pipes, channels, wells, cavities...

- for pipes from \varnothing 70 to \varnothing 300 mm diameter
- 87° bendable form \varnothing 100 mm
- Push cable with flexible cables and glass fiber core, - very durable!
61m long and \varnothing 10 mm diameter

SPECIFICATION

- **Camera:**
 - stainless steel
 - diameter \varnothing 50 mm
 - water resistant up to 6 bars
- **Lighting:**
 - 40 pcs, \varnothing 3 mm ultra-bright white LED's
 - Light smooth adjustable
- **Objective:**
 - 130° wide angle
 - depth of field from 5 cm to infinity
 - manually adjustable
- **Cameramodule:**
 - high resolution $\frac{1}{4}$ " Chip
 - 795 (H) x 596 (V), 655 TV
- **Image:**
 - always upright picture
- **Frame:**
 - steel tube, galvanized and powder coated
 - 6 pins slip ring
 - smooth adjustable brake
 - transport wheels
 - aluminum control box with integrated power- supply for camera and light control
 - robust cable management
 - holder for adaptors
 - fiberglas push cable: 61 m long / \varnothing 10 mm
- **Power supply:**
 - AC: 110 V / 60 Hz, 240 V / 50 Hz
 - DC: +18 V / 40 W
- **Dimension:**
 - width: 63 cm / depth: 34 cm / height: 73 cm
 - weight: app. 19 kg

OPTIONS

- **Plug-in camera connection**
- **Location Transmitter**
 - integrated in the camera head
 - frequency range: 32,7 kHz
- **Meter counter:**
 - with video overlay
- **Texgenerator with meter counter:**
 - video text overlay and meter counter
 - with 16 lines and 30 characters
 - several languages
 - CCTV-inspection software
 - PS/2-keyboard interface
- **Keyboard:**
 - PS/2 or USB Connection
- **Controll unit**
 - integrated battery
 - 3,5 A / 19 V / Lithium-Ion
 - dimensions: L: 22 / W: 15 / H: 8 cm
 - weight: +1 kg
- **Digital Video Recorder**
 - video: AVI / 960 x 576 / 25 fps
 - image: JPG / 960 x 576
 - remote control
 - micro SD max. 256 GB- or USB max. 1 TB
- **Digital Video Recorder HD**
 - video: MPEG4 / 1920 x 1080 / 30fps
 - quick recording by one push button
 - image: JPG / 1920 x 1080
 - remote control
 - SD card, max. 32 GB / USB, max. 2 TB



ACCESSORIES

The Company **CTU** is your experienced partner for sewer and pipe cameras. All camera systems come from own development and production. We place a special emphasis on quality and a robust, service-friendly processing. Thanks to our many years of experience, we can offer you a suitable solution for every application at a reasonable price.



CTU

Camera Technic Ujvari



Stadtbadstraße 52
87439 Kempten
Germany

Tel.: +49(0)831 5123281
E-Mail: info@ctu-a.de
Web: www.ctu-a.de

- **5,6" LCD-Display**
 - resolution: 320 x 234
 - brightness: 350
 - contrast: 350:1
 - housing
 - alumin, powder coated
 - on ball joint
 - dimension: 15 x 12 x 4,5 cm
 - weight: app. 0,5 kg



- **5,6" LCD-Display**
 - resolution: 640 x 480
 - brightness: 400
 - contrast: 500:1
 - housing with cover
 - alumin, powder coated
 - on ball joint
 - dimension: 16 x 12 x 5 cm
 - weight: app. 0,8 kg
 - options:
 - digital video recorder



- **8" LCD-Display HD**
 - resolution: 1024 x 768
 - brightness: 400
 - contrast: 400:1
 - housing with cover
 - alumin, powder coated
 - on ball joint
 - dimension: 21 x 15 x 6cm
 - weight: app. 1 kg
 - options:
 - digital video recorder HD



- **10" LCD-Display HD**
 - resolution: 1024 x 768
 - brightness: 400
 - contrast: 400:1
 - case: alumin / plastics
 - dimensions: 34x29x15cm
 - weight: app. 3 kg
 - options:
 - digital video recorder HD
 - keyboard



ADAPTOR

- Sliding sleeve
 - for pipes from \varnothing 80 mm
 - \varnothing 65 mm, L: 49 mm
- Sliding sleeve
 - for pipes from \varnothing 100 mm
 - \varnothing 80 mm, L: 49 mm
- Roller carriage
 - for pipes from \varnothing 125 mm
 - \varnothing 114 mm, L: 195 mm
- Roller carriage
 - for pipes from \varnothing 150 mm
 - \varnothing 136 mm, L: 195 mm
- Roller carriage
 - for pipes from \varnothing 200 mm
 - \varnothing 178mm, L: 221 mm
- Roller carriage adjustable
 - for pipes from \varnothing 300 mm- to \varnothing 500 mm
 - \varnothing 280 / 480 mm, L: 350 mm

