

PIPE INSPECTIONS SYSTEM

B.2730

SPECIFICATION

OPTIONS



- **Camera:**
 - stainless steel
 - diameter \varnothing 27 mm
 - water resistant up to 5 bar
- **Lighting:**
 - 21 pcs, \varnothing 3 mm ultra-bright white LED 's
 - Light smooth adjustable
- **Objective:**
 - 150° wide angle
 - Depth of field from 3 cm to infinity
 - manually adjustable
- **Cameramodule:**
 - high resolution $\frac{1}{4}$ " Chip
 - 795 (H) x 596 (V), 655 TV
- **Frame:**
 - plastic
 - 6 pins slip ring
 - smooth adjustable brake
 - aluminium control box with integrated power supply, camera and light control
 - multi-wire cable
30 m up to 150 m long / \varnothing 7mm
- **Power supply:**
 - AC: 110 V / 60Hz, 240 V / 50 Hz
 - DC: +18 V / 40 W
- **Dimension:**
 - width: 31 cm
 - depth: 27 cm
 - height: 36 cm
 - weight: app. 5 kg

- **Sliding camera for optical inspection of pipes, channels, pipes, wells, cavities**
 - for pipes from \varnothing 40 to \varnothing 150 mm
 - 87° bendable from \varnothing 50 mm
 - cable length of 30 m up to 150 m / \varnothing 7 mm

- **Location Transmitter**
 - integrated in the camera head
 - frequency range: 32,7 kHz



- **Meter counter unit**
 - cable routing with pulse generator
 - Waterproof



- **Meter counter:**
 - with video overlay



- **Texgenerator with meter counter:**
 - video text overlay and meter counter
 - with 16 lines and 30 characters
 - several languages
 - CCTV-inspection software
 - PS/2-keyboard interface



- **Keyboard:**
 - PS/2 or USB Connection



- **Controll unit**
 - integrated battery
 - 3 A / 19 V / Lithium-Polymer
 - dimensions: L: 22 / W: 15 / H: 8 cm
 - weight: +1 kg



- **Digital Video Recorder**
 - video: AVI / 960 x 576 / 25 fps
 - image: JPG / 960 x 576
 - remote control
 - micro SD: max. 256 GB / USB: max. 1 TB



- **Digital Video Recorder HD**
 - video: MPEG4 / 1920 x 1080 / 30fps
 - quick recording by one push button
 - image: JPG / 1920 x 1080
 - remote control
 - SD card: max. 32 GB / USB: max. 2 TB



ACCESSORIES

The Company **CTU** is your experienced partner for sewer and pipe cameras. All camera systems come from own development and production. We place a special emphasis on quality and a robust, service-friendly processing. Thanks to our many years of experience, we can offer you a suitable solution for every application at a reasonable price.



• 5,6" LCD-Display

- resolution: 320 x 234
- brightness: 350
- contrast: 350:1
- housing
alumin, powder coated
- on ball joint
- dimension: 15 x 12 x 4,5 cm
- weight: app. 0,5 kg



• 5,6" LCD-Display

- resolution: 640 x 480
- brightness: 400
- contrast: 500:1
- housing with cover
alumin, powder coated
- on ball joint
- dimension: 16 x 12 x 5 cm
- weight: app. 0,8 kg
- options:
digital video recorder



• 8" LCD-Display HD

- resolution: 1024 x 768
- brightness: 400
- contrast: 400:1
- housing with cover
alumin, powder coated
- on ball joint
- dimension: 21 x 15 x 6 cm
- weight: app. 1 kg
- options:
digital video recorder HD



• 10" LCD-Display HD

- resolution: 1024 x 768
- brightness: 400
- contrast: 400:1
- case: alumin / plastics
- dimensions: 34x29x14 cm
- weight: app. 3 kg
- options:
digital video recorder HD
keyboard



ADAPTOR

• Sliding sleeve

- for pipes from \varnothing 50 mm
- \varnothing 40 mm, L: 34 mm



• Sliding sleeve

- for pipes from \varnothing 80 mm
- \varnothing 60 mm, L: 34 mm



• Adaptor sleeve

- for roller carriage
- \varnothing 50 mm, L: 34 mm



• Roller carriage

- for pipes from \varnothing 125 mm
- \varnothing 114 mm, L: 195 mm



• Strain relief

- for all roller carriage



• Spring clutch

- for push rods
- \varnothing 12 mm, L: 150 mm



CTU

Camera Technic Ujvari



Stadtbadstraße 52
87439 Kempten
Germany

Tel.: +49(0)831 5123281
E-Mail: info@ctu-a.de
Web: www.ctu-a.de